



APPROVAL SHEET

Universal AC Adapter

MODEL NO: SP-AD-120W-E



Article No. : SP-AP-SU-A122 Issue Date :2010-10-11 Version : A/0	Audited by
Checked by	Drafted by

Spire Corp.

Tel.: +86-755-26801567 Fax: +86-755-26801561

[Http://www.spire-corp.com](http://www.spire-corp.com)

[Http://www.spirepower.com](http://www.spirepower.com)

[Http://www.spirecoolers.com](http://www.spirecoolers.com)



Spire Corp.

Contents

1	Description.....	3
2	Specification.....	3
3	Input Characteristics.....	3
4	Output Characteristics.....	4
5	Protection Requirement.....	5
6	Environmental Requirement.....	5
7	Mechanical Requirement.....	6
8	Correlative Certification compliance.....	6
9	Compatible List.....	7
10	Pictures.....	8



1 Description

This model is an universal switching-mode power supply for Laptop and USB, operation at input AC to DC and DC to DC 2 in 1:AC input 100V ~240V 47-63Hz, DC input 11~15V. Output USB port:5V@1A max. Output DC 7 voltages: 15V/16V/18V/19V/20V@6.0Amp max, 22V/24V@5.0Amp max Output power 120 Watt max, with protection: Overload protection, Short Circuit Protection. With 8PCS tip connector to suit to almost Laptops, Select output voltage to suit to Laptop and make sure the polarity of tips connect correct before use.

2 Specification

1.Input:

AC rated input voltage:100~240V,AC input rated current 1.8Amp.

DC rated input voltage:11!15V,DC input rated current 14A

2.Output Voltage: 15V/16V/18V/19V/20V DC at 6.0 A max or 22V/24V DC at 5.0 A max

3.USB Output: 5V-1

4. With 8 pcs interchangeable tips can use for mostly netbook/Laptop models and PDA/MP3/MP4/iPod

5. Power:120W MAX (For home and car use).

6. Provides power supply to a wide range of notebooks Overload, short circuit and overheat protection

3 Input Characteristics

3.1 Input Voltage:

Nominal Voltage:100-240Vac

Variation Range :90-264Vac

3.2 Input Frequency:

Nominal Frequency:50/60Hz

Variation Frequency:47-63Hz

3.3 Input Current:

The maximum input current shall be less than 1.8A at 100~240Vac input

3.4 Output Current:

The maximum output current shall be less than 6.0A at 100~240Vac

input,15V/16V/18V/19V/20V output and 5.0A at 100~240Vac input, 22V/24V output

3.5 Efficiency:

80% min. measured at 100Vac and 240Vac input voltage, rated load



4 Output Characteristics

4.1 Rated Voltage

The adapter shall have one regulated DC output of 15V/16V/18V/19V/20V/22V/24V

When the output voltage is 15V, the rated voltage: 14.3V—15.7V.

When the output voltage is 16V, the rated voltage: 15.2V—16.8V.

When the output voltage is 18V, the rated voltage: 17.1V—18.9V.

When the output voltage is 19V, the rated voltage: 18.1V—19.9V.

When the output voltage is 20V, the rated voltage: 19.0V—21.0V.

When the output voltage is 22V, the rated voltage: 20.9V—23.1V.

When the output voltage is 24V, the rated voltage: 22.8V—25.2V.

4.2 Rated Output Current

At CC mode:

When the output voltage is 15V, the output current will be less than 6.0A.

When the output voltage is 16V, the output current will be less than 6.0A.

When the output voltage is 18V, the output current will be less than 6.0A.

When the output voltage is 19V, the output current will be less than 6.0A.

When the output voltage is 20V, the output current will be less than 6.0A.

When the output voltage is 22V, the output current will be less than 5.0A.

When the output voltage is 24V, the output current will be less than 5.0A.

4.3 Rated Power

This adapter is capable to support 120Watts continuously at all specified conditions.

4.4 Ripple & Noise Voltage

Voltage	15V/16V/18V/19V/20V/22V/24V at full load	
Ripple & noise voltage	1000mV	



The ripple and noise are as follows when measure with Max. Bandwidth of 20MHz and Parallel 10uF/0.1uF, crossed connected at testing point.

4.5 Hold-UP Time

The voltage reach down to 2V at CC mode more than 1ms after at AC voltage turned off.

4.6 Output voltage rise time

The rise time of all outputs voltage shall be less than 500mS measured from 10% point to 90% point.

4.7 Turn on delay time

3 second maximum from ac input to all outputs within regulation.

5 Protection Requirement

5.1 Short Circuit Protection:

The adapter is protected that a short happened between the output terminals and shall not result in a fire hazard, any damage to this adapter and will be normal operation automatically while the short is removed.

5.2 Over Voltage Protection

The unit must shutdown when output voltages detect OVP point and the unit shall not be damaged.

Output Voltage	15V/16V/18V/19V/20V/22V/24V
OVP Point	30VDC

6 Environmental Requirement

6.1 Thermal Performance

Operating : 0°C ~40°C

Non-operating : -20°C ~70°C

6.2 Humidity

Operating : 20% to 80%RH.

Non-operating : 10% to 90%RH.



7 Mechanical Requirement

7.1 **Dimension:** 156mm*64mm*38mm

7.2 **Weight:** 384g±5g

7.3 **Output Cord:** 1.2M EU AC Cable

7.4 **Plug:**

Tip A - 6.0mm*4.4mm	Black
Tip B - 6.3mm*3.0mm	Green
Tip C - 5.5mm*2.5mm	White
Tip D - 5.5mm*2.1mm	Blue
Tip E- 5.5mm *1.7mm	Yellow
Tip F- 4.8mm* 1.7mm	Yellow
Tip G - 4.0mm* 1.7mm	Yellow
Tip H - 5.0mm x 3.4mm	Yellow

8 Correlative Certification compliance

Item #	Certification type	Certification Number	Certification listing	Remark
1	CE-EMC	BST10120427EC -1	WWW.BST-LAB.COM	
2	CE-LVD	BST10120427SC -2	WWW.BST-LAB.COM	

9 Compatible List



Connector Using Instruction

TIP	DC TIP SIZE	Notebook Model
A	6.0mm*4.4mm Black	Fujitsu/SAMSUNG/SONY
B	6.3mm*3.0mm Green	Toshiba/NEC
C	5.5mm*2.5mm White	Fujitsu/ Toshiba/ ACER/DELL/ IBM/HP/ Compaq/ ASUS
D	5.5mm*2.1mm Blue	Compaq/ BENQ/ ACER/IBM/HP/NEC/ Toshiba/
E	5.5mm*1.7mm Yellow	ACER/ HP
F	4.8mm*1.7mm Yellow	HP/NEC/ ASUS/ Compaq
G	4.0mm*1.7mm Yellow	ACER/ ASUS/BENQ/SONY
H	5.0mm*3.4mm Yellow	SAMSUNG



Spire Corp.

10 Pictures:




Best Service of Testing

Certificate of Compliance

Certificate Number : BST10120427EC-1

Applicant : Bytecom Fanner B.V.
Rondven 38, 6026PX Maarheeze The Netherlands

Manufacturer : SPIRE SHENZHEN CORP.
FL7/8 Building B houhai Blvd Dongjiaotou Industrial Park
Shekou, Nanshan 518067 Shenzhen, China

Product M/N : UNIVERSAL AC ADAPTER
SP-AD-090W-E, SP-AD-090W-EU, SP-AD-090W-E2,
SP-AD-120W-E, SP-AD-120W-E2, SP-AD-120W-EU-1,
SP-AD-090W-EU-2, SP-AD-120W-EU, SP-AD-120W-EU-2

Test Standard : EN 55022:2006+A1:2007
EN 61000-3-2:2006+A2:2009
EN 61000-3-3:2008
EN 55024:1998+ A2:2003

The EUT described above has been tested by us with the listed standards and found in compliance with the council EMC directive 2004/108/EC. It is possible to use CE marking to demonstrate the compliance with this EMC Directive.
The certificate applies to the tested sample above mentioned only and shall not imply an assessment of the whole production. It is only valid in connection with the test report number: BST10120427ER-1.




Christina
Manager
Dec. 30, 2010

Shenzhen BST Technology Co., Ltd.
3F, Weames Technology Building, No. 10 Kefa Road, Science Park, Nanshan District, Shenzhen, Guangdong, China
Tel: 86-755-26747751~3 (100 lines) Fax: 86-755-26504032 <http://www.bst-lab.com>



Best Service of Testing

Certificate of Compliance

Certificate Number : BST10120427SC-2

Applicant : Bytecom Fanner B.V.
Rondven 38, 6026PX Maarheeze The Netherlands

Manufacturer : SPIRE SHENZHEN CORP.
FL7/8 Building B houhai Blvd Dongjiaotou Industrial Park Shekou,
Nanshan 518067 Shenzhen, China

Product : UNIVERSAL AC ADAPTER

M/N : SP-AD-090W-E, SP-AD-090W-EU, SP-AD-090W-E2,
SP-AD-120W-E, SP-AD-120W-E2, SP-AD-120W-EU-1,
SP-AD-090W-EU-2, SP-AD-120W-EU, SP-AD-120W-EU-2

Test Standard : EN 60950-1:2006+A11:2009

The EUT described above has been tested by us with the listed standards and found in compliance with the council LVD directive 2006/95/EC. It is possible to use CE marking to demonstrate the compliance with this LVD Directive.

The certificate applies to the tested sample above mentioned only and shall not imply an assessment of the whole production. It is only valid in connection with the test report number: BST10120427SR-2.



Christina
Manager

Dec. 31, 2010

Shenzhen BST Technology Co., Ltd.

3F, Weames Technology Building, No. 10 Kefa Road, Science Park, Nanshan District, Shenzhen, Guangdong, China

Tel: 86-755-26747751~3 (100 lines) Fax: 86-755-26504032 <http://www.bst-lab.com>



Spire Corp.

Spire Coolers Corp.
FL7/8 Building B houhai Blvd
Dongjiaotou Industrial Park Shekou
Nanshan, Shenzhen, China
Tel.: +86-0755-26801567
Fax: +86-0755-26801561
W.: www.spire-corp.com



RoHS Declaration of Conformity

Spire hereby declares under our sole responsibility that the product:

Part number: **SP-AD-120W-E**

Description: AC Input: AC100--240V 1.8A;

Output voltage: 15V/16V/18V/19V/20V

DC at 6 A max or 22V/24V DC at 5 A

max,Power:120W MAX,USB Output: 5V/1A



Is tested and approved in compliance with the EUROPEAN COUNCIL ROHS DERECTIVE.

(Restriction of Hazardous Substances) which will restrict the use of certain substances in electrical and electronic products: including lead (Pb), mercury, cadmium, hexavalent chromium, and certain halide-containing flame retardants. The directive applies to all electrical and electronic products, their component parts that are placed on the market after July 1, 2006.

Spire Coolers Corp.
PM Engineering Dept.

Nanshan, Shenzhen

